




Designed by Barba Corsini & Joaquim Ruiz Millet

PRODUCT COLOURS





Item no.: 003-0410X + style code

DESCRIPTION

In 1955 Barba Corsini renovated the loft space within Antoni Gaudi´s famous building "La Pedrera" in Barcelona, transforming it from a simple laundry room and storage area into 13 modern duplex apartments. To reinforce the modernist style of the rooms, Corsini decorated the apartment with furniture that he designed himself, including Pedrera lamps and tables. The inspiration for the base of the lights came from the vaulted ceilings of the famous house of "la Pedrera" whilst the cylindrical shape and unique, perforated detail of the chimneys influenced the form of the lampshades.

VERSION - PEDRERA ABC TABLE LAMP / Ø18.5 PD4

- Fabric wire White:
- Matt white // RAL 9003 // Gloss level 20
- Blue // RAL 5010 // Gloss level 30
- Red // RAL 3020 // Gloss level 30 $\,$
- Fabric wire Black:
- Matt black // RAL 9005 // Gloss level 20

PENDANT VERSION

Order item - look for part number in the pricelist.

Series contains the following:

PD1 PD3, PD2, PD4 PD5

FACTS

MEASUREMENT - L X W X H MM Lamp height: 355 mm Shade diameter: Ø185 mm Cable length, exposed: APP. 2000 mm

WEIGHT ITEM - *LAMP INCL. WIRE* 1224 g

PACKAGING TYPE Cardboard box

PACKAGING MEASUREMENT - L X W X H CM L:20,5 X W:20,5 X H:41 cm

WEIGHT PACKAGING - MATERIAL TYPE

- Delivery note: 4 g
- Plug protector: 15 g
- Plastic bags (PE-LD + PO-HD): 24,5 g
- Plastic bags (PE-LD + PO-HD): 10,5 g
- Cardboard bottom: 66 g
- Cardboard: 270 g

WEIGHT PACKAGING - TOTAL 1615 g



ACCESSORIES	NUMBER OF PARCELS - SALES PACKAGING
Exchangeable Inner Shade ENVIRONMENT	1 pcs. NUMBER OF PARCELS - TRANSPORT PACKAGING 1 pcs.
-	PACKAGING MEASUREMENT - L X W X H CM
TESTS	-
-	BULB REQUIREMENTS - Socket: E27 base - Recommended light source: Halogen light bulb
CERTIFICATION AND LABELS	- Recommended wattage: 28 W
CE-Declaration	- Max. wattage: 42 W
	* Lightbulb not included.
	- Euro plug: Type C, 2 PlN, 2,5 amp - Euro voltage: 230 V



Class II / Double insulated

- Freqvency: 50 Hz - Supply voltage: AC power ~ - Normally Closed IP20

CE-Mark

F

Luminaires accepted for mounting on a flammable base